



RIPPLE

PRODUCT DESCRIPTION

An acrylic copolymer based paint, designed for textured finish.

PRODUCT FEATURES

Ripple is a flexible coating for use on exterior & interior surfaces. Ideal for covering wall blemishes & hairline cracks.

TECHNICAL INFORMATION

- Colour: White & Pastel colours
- Appearance: Textured when applied with Ripple Roller
- Generic type: Acrylic copolymer emulsion
- Pigment type: Titanium dioxide
- S.G.: ±1.45
- Viscosity: ±130ku
- Spreading rate: ±1-2 m²/litre
- Solvent: Water
- Washability: 10 000 scrubs minimum
- Mix ratio: Single pack ready for use
- Packaging: 1 litre, 5 litre, 20 litre plastic containers

SURFACE PREPARATION

Always ensure the substrate is clean, dry and free of contaminants e.g. oil, grease, wax, dirt, etc. prior to application of Ripple. On very absorbent surfaces it is recommended to apply a first coat of Acrylic Sealer or Bonding Liquid. Flaking paint is to be removed. The surface is then to be sanded or wire brushed, prior to application of one coat of Acrylic Sealer or Bonding Liquid, then primed with Super Acrylic 300. Then apply 1 coat of Ripple. Always abide by over coating times.

APPLICATION

New plaster should be cured, dry, and free of grease, oil or other contamination & primed with Super Acrylic300. Old paint work, remove all loose & flaking paint, sand with P80 paper or wire brush to sound surface. Apply 1 coat Acrylic Sealer or Bonding Liquid. Allow to dry, prime with Super Acrylic 300. Use a textured roller only. Load the roller well & spread the paint well. Work with small areas in time. Do not roll out too thinly. Finish off vertically working from bottom to top. Use light pressure.

- Airless spray: Not recommended
- Conventional spray: Not recommended
- Brush and Roller: Suitable as supplied. Special roller required, ask sales assistant for details
- Clean up: Do not allow to dry on or in equipment, wash immediately with water

ENVIRONMENT

At no time should paint be applied outdoors in inclement weather or before 9 am and after 2 pm in winter. Do not leave container open as a skin forms on the surface of the paint. It is recommended that application be confined to the following:

- Surface temperature: Min. 10°C Max. 40°C
 - Ambient temperature: Min. 10°C Max. 40°C
 - Relative humidity: Min. 0% Max. 85%
- Or at least 3°C above Dew point

DRYING TIME

| Substrate Temp | Touch Dry | Hard Dry |
|----------------|------------|----------|
| 15°C | 3 hours | 18 hours |
| 20°C | 1 hour | 12 hours |
| 25°C | 40 minutes | 8 hours |
| 30°C | 30 minutes | 4 hours |

OVERCOATING TIMES

- 15°C: 24 hours
- 20°C: 16 hours
- 25°C: 10 hours
- 30°C: 8 hours

STORAGE AND HANDLING

Store in a cool dry area, away from heat, direct sunlight and severe cold.
Shelf life: 18 months in original sealed containers.

LIMITATIONS

Sustained cold conditions can result in paint failure. Avoid painting on wet substrates and in wet conditions. In extreme cold conditions such as temperatures below 5°C, Ripple becomes very viscous & difficult to roll. For best results, leave product outside in the sun & start application not earlier than 10 am.

SAFETY PRECAUTIONS

No known problems resulting from contact with skin, however, remove as soon as possible with soap and water. Avoid ingestion and contact with eyes. If ingested seek medical attention. Do not induce vomiting. If paint contact is made with eyes, rinse eyes well with water and seek medical attention. Do not smoke when painting. Ensure good ventilation during painting and drying.
KEEPOUTOFREACHOFCHILDREN.

Information Provided is based on Laboratory evaluations and data believed to be reliable.
 Recommendations are given in good faith but without warranty. It is the user's responsibility to determine the suitability for their own use.
 It is not to be considered a guarantee of the products properties.
 For more information contact our Factories:
Western Cape: Tel/Fax: (021) 853-8105 **Mpumalanga:** Tel: (013) 246-2570 Fax: (013) 246-2573